

Automation System
ANISO 9001 - 2008 GERTIFIED GOMPANY




















Automation System
ANISO 2001 - 2003 GERTIFIED COMPANY

Varieties of Rolling Shutters Profile Section


























Automation System

Dear Customer

We are Manufacturers of Rolling Shutters. Now, it is one of the leading Rolling Shutter Manufacturers in South India. JAI BHAVANI BRAND has become a Hall Mark for its quality in the market. Automatic equipments that are problem free and easy to operate. We believe these products to be the most technically advanced systems in the market for almost any application you might envision.

Central Install Spring Balance Rolling Shutter Motor

IS 6248 standard
Smooth noiseless function
Easy and fast installation
Suitable for both new and existing shutters
IP level 54
Electro magnate brake help as anti fall system
Wide range of model available from 150 to 2500 kg
Motor protected with internal thermal switch
Easy manual override in case of power failure
No bulky visible outside.







Springless Rolling Shutter Side Motor





Automation System

Rolling Shutters

Rolling Shutters are Simple and Good Shutters type: Manual, Mechanical & Motorized, MS at GI Metals IS 6248 standard Smooth noiseless function Easy and fast installation

Suitable for both new and existing shutters Wide range of model available from 150to 3000kg

Motor protected with internal thermal switch

Easy manual override in case of power failure No bulky visible outside thanks to compact model.

Available Size 15m x 15m.

Available Lath Section 1.2 mm, 1 mm, 0.9 mm, 0.8 mm Also Available in Semi Flat & Full Flat Type Profile Sections



PUSH & PULL TYPE ROLLING SHUTTERS











Automation System

AN ISO 9001 - 2008 GERTIFIED GOMPANY

Perforated Rolling Shutter 'C' Thru Shutter & Grill Type

Shutters type: Manual, mechanical & motorized Perforated Rolling Shutter are visible type shutters

IS 6248 standard

Smooth noiseless function

Easy and fast installation

Suitable for both new and existing shutters

Wide range of model available from 150 to 2000 kg

Motor protected with internal thermal switch

Easy manual override in case of power failure

No bulky visible outside

Available Power Coating (Any Colours)

Available GI MS Metals

Available Lath Section Thick

1.2 mm, 1.00, 0.9 mm, 0.8 mm

"C" Through hole dia 2 mm / 3 mm

Grill Type & Pipe Grill Rolling Shutters

Available in MS, GI, Aluminium, SS Metals












Automation System

AN ISO 9001 - 2008 GERTIFIED COMPANY

Manual Gear Operated Rolling Shutter

Providing and Fixing in position rolling shutters of approved make as per IS 6248, made of 75 × 18g M.S. laths interlocked together through their entire length and jointed together at the end by end locks mounted on specially designed pipe shaft with brackets, side guides, and arrangements for inside and outside locking with Manual, Mechanical gear operated & electrical operated.



Motor Make : Jie long, Strong Life (made in China) Nice, Elero, Came, Allmatic, (made in Italy & Germany)

Poly Carbonate Rolling Shutter Acrylic

Poly Carbonate Rolling Shutter are Stylish and Transparent model. Polycarbonate is a man made material that's especially suitable for roller shutters. Like glass, it's transparent, but unlike glass, it's very hard to break. Wide range of model available from 150 to 2000 kg.

Motor protected with internal thermal switch.

We can do Only Motorised for polycarbonate rolling shutters.









Automation System

AN ISO 9001 - 2008 CERTIFIED COMPANY

Hi Speed Roll Up Door



To be install at loading / Un loading Bays It protects from Cooling Losses, Dust, Sun Rays & Pesticides Inflatable Dock shelter for a wide variation in vehicle sizes. Cushion type Dock shelter for cold Room application Retractable Dock Shelters for Normal Bays.



Imported from ITALY, for heavy Industrial use and for quick opening and closing application for high traffic zones inside and outside the plant.

Available in GI/SS/food Grade doors

PVC doors available from 0.9MM to 3 MM thickness Available for normal sizes / Big opening and giant Doors up to 10 Mtr x 10 Mtr.

The doors are compliant with European Standard - 13241/EN.



Special PVC or Polyester, self - extinguishing curtain available in wide range of colours. Opening speed up to 1.1m/s.

> Drop proof safety and ACS crash - proof system Emergency lock release handles available on both sides Easily interchangeable sections

Simple, functional control panel with ' self test' functions Innovative curtain self - repair ability system

Suitable for food industry, pharmaceutical, electronic, textiles, refrigerated factory, printing industry, precision machines & automobile installation.









Automation System

AN ISO 9001 - 2008 GERTIFIED COMPANY

Industrial Metal Door

Doors

All door leafs shall be 50/65/70 mm, double skinned galvanized, commercial grade steel G90, zero spangle to B.S.2989 made of 1.0mm thick face sheets and solid core construction of compressed mineral wool infill 100k.g./m3 density filled in between reinforcing stiffners and 2mm lead sheets, 3mm acoustic sheet. Door leafs shall be rebated on 3 sides. Doors shall achieve sound reduction index varying from 35db to 45db at 4KHz octave brand.



Industrial Over Head Sectional Door

Imported from the best company in Europe Available in Horizontal, vertical and special model for less lintel height

Thickness 42 MM maximum size available 8 Mtr x 6 Mtr Also can be inter locked with Dock leveler European Standard 13 241/EN.





Garage Door

Ceiling Mounted Sleek operated with state – of – the – art encoder technology and with courtesy light. Pre – printed, Galvanized steel sandwich panels or sandwich panels with solid wood load – bearing Remote control Operation

Range of standard and optional safety devices like pinch – proof guard, spring anti – break safety device, cable and anti - break device, Safety edge etc. Helps in sound – proofing and thermal insulations.

Prime Quality



Best Designed



Automation System



Sliding Gates

Smooth noiseless function Easy manual over ride incase power failure Adjustable torque IP level 54 For safety auto Stop & auto reverse facility with advance control unit In built Control unit with internal Thermal Switch Model Available from 400 kg to 3000 kg Capacity



Telescopic Gate







Sliding Gate Operated Motor Set



Warranty



Guarantee



Automation System

Swing Gate

Operated protected with internal thermal switch

Wide range of model available from 3 mtrs to 10mtrs

Also available under ground / for wide pillar & for outside opening Smooth noiseless function

Easy manual over ride incase power failure

Adjustable torque IP level 54

For safety auto Stop & auto reverse facility with advance control unit

In built Control unit with Internal Thermal Switch

Model Available from 400 kg to 2000 kg Capacity

In built Control unit with internal Thermal Switch













Automation System
ANISOSON -2003 GERMANY

Retractable Gate

Smooth noiseless function

Also available Telescopic Collapsible gates \$5 304 & Aluminium

Retractable gates: SS 304 size 9 max 9 mtrs x 1.5 mtrs)

Fabrication Of gates of different design







W

JAI BHAYANI ENGINEERING WORKS

Automation System

AN ISO 2001 - 2008 GERTIFIED COMPANY

Automation Accessories

Smooth Noiseless Function

Easy Manual over Ride Incase Power failure

Adjustable Speed IP level 54

Wide Range of Model for various applications like

Toll Collection, Theratre, Shopping Mall,

Car Parking & Hospital Etc.

From 2.5 mtrs to 8 mtrs, Possible opening of 16mtrs Length.

Available in powder coating, Aluminium & Stainless Steel.

Slow down Function when closing / Opening.

Battery backup also available.

Available LED lights

Detection of Obstacle & Reopening with Automatic Device.



Sterriers strudele BOYK per Faulumentens di percheggi conduminiali e industriali. Appli berrier







Boom Barriers





Des ets direction federalisations		EN	804	-		NO.
Division in magi		37to D4	20% (E%		ΨIJ	1
Diretalmenter drys magil		316	376			
Suddown store or days or	M					
New roles Stirger	M	38	-	41.0	**	
Kalagis Alle mels on	let.	100	100			1.171
No High	N					
Imprigation Spring to	[m]				ы	
Digentinospi. Nomental til mek ox	(4)	100	100	1.8.3	- 4	
inglescresioniers a intringital of	M				,	
Senior Senior	N			-	- 0	_
Sepreture of Septembers - No Ingrespondum	79	44	24	4 1	-	
strikensine hate prigar				March	- 43	1



700 Jai Bhavani Engineering Works

Automation System

Fire Door

Fire Doors available in 1, 2 & 3 hrs rating available in MS / Wooden.

IS 3614 Standard.

Accessories Like: Panic Bar / Vision Window.

Dead Lock / Mortise Lock / Door Closer.



General Fabrications

- 1. Grill Works for SS, MS & Casting
- 2. SS & MS hand Rail
- 3. Steel windows
- 4. Collapsible gates
- 5. Book doors
- 6. Light Roofing shed
- 7. Heavy Structural Fabrications
- 8. Truss Works
- 9. Pup Shed
- 10. Column Box
- 11. Centering Sheet works











Automation System
ANISO 2003 GERTIFIED COMPANY

Accessories

Key Box



Push Button



Key Switch



Push Button Switch



Remote Control



Control Unit



Radio Receiver Remote


















Automation System

AN ISO 9001 - 2008 CERTIFIED COMPANY

Accessories















We are the Dealers of



















Our Clients

























































JAN BHAVANI ENGINEERING WORKS

Automation System

AN ISO 9001 - 2008 GERTIFIED COMPANY

JAI BHAVANI BRAND REOWNED FOR SAFETY & SECURITY Corporate Office

No: 308, C - Block, Ramalinga Colony, Thanikachalam Nagar, (Near Kumaran Nagar Bus Stand) Chennai - 600110, Tamil Nadu, India. TeleFax: 044 – 25560467 / 68. | Mob: 9841099624 / 9840981087 Branch Office

Bangalore Address: Govindappa Building, Muneshwara Nagar, Kammasandra Cross, Hebbagodi, Anekal Taluk, Bangalore - 560099. Contact No: +919841099624 / +919036338339

Email: jaibhavanienggworks@gmail.com | jaibhavaniengineering@yahoo.co.in Website: www.jbew.in | www.jaibhavanishutters.com

http://www.indiamart.com/jai-bhavani-engineering-works